

Art 1860 - SWING WAFER CHECK VALVES

Available with carbon steel body suitable for heating and conditioning purposes, water treatment and distribution, agricultural applications, compressed air circuits, oils and hydrocarbons.

Available in stainless steel CF8M suitable for chenmical plants, food processing and general industrial purposes.


DIN or ANSI flanges compatibility




	Componente - Component	Materiale - Material
1	Corpo - Body	Acciaio inox - Stainless steel ASTM A351 gr. CF8M / Acciaio al carbonio - Carbon steel ASTM A216 gr. WCB
2	Disco - Disc	Acciaio inox - Stainless steel ASTM A351 gr. CF8M / Acciaio al carbonio - Carbon steel ASTM A216 gr. WCB
3	Piastrina DN32-250 - Plate DN 32-250	Acciaio inox - Stainless steel ASTM A351 gr. CF8M
4	Piastrina DN300-400 - Plate DN 300-400	Acciaio inox - Stainless steel AISI 316
5	O-Ring - O-ring	NBR, FKM (Viton®), PTFE
6	Molla - Spring	Acciaio inox - Stainless steel AISI 302
7	Occhiello a vite - Eyebolt	Acciaio inox - Stainless steel AISI 316
8	Viti - Screw	Inox A2 - Stainless steel A2


DN 32 - 250











DN	32	40	50	65	80	100	125	150	200	250	300	350	400
P	20	26,5	33	43	53	75	96	118	164	200	245	284	323
A	16	16	18.5	18.5	22	23.5	29	34.5	36	38	32	38	42
С	77	86,5	99	118	134	154	184	208	264	317	280	440	490
Н	83.5	88.75	98,5	107	115	131	138	137	169	247	-	-	-
H1	45	49	53	63	73	92	119	149	167	140	-	-	-
Q.	21	24	36	49	58	77	95	117	151	183	243	260	306

*Valore di massima. La quota effettiva dipende dalle dimensioni del tubo.

*For information maximum dimension. Actual dimension depend on pipe dimension.

kg	0.43	0.54	0,82	1,25	1,86	2,42	3.1	5.3	8.5	12,4	17,6	27.8	36,1